

# IPC2252-FN/FNB-PIR50-Z2812

## 2.0MP Starlight & Ultra WDR HD Network Varifocal IR Bullet Camera



### Features

#### Excellent Image Quality

- 2,073,600 pixel 1/2.8" progressive scan CMOS sensor
- High definition and smooth picture, 1920x1080p@30fps
- H.265 video codec, saves up to 50% bandwidth and storage
- Ultra low illumination, 0.002lux with color picture
- 120dB Ultra WDR
- 3D noise reduction / Auto Iris / HLC

#### Intelligent Functions

- Motion detection / Tampering / Guard line / Enter guard area / Exit guard area

#### Integrated High Efficiency IR

- Industrial IR LED with long operational lifespan
- 50 ~ 70m IR distance
- Smart IR function

#### A Variety of Installation Modes

- Supports 90°, 180°, 270° image rotation
- Motorized varifocal lens

#### Abundant Functions and Features

- Micro SD card slot, supports Automatic Network Replenishment (ANR) 3.7
- Up to 3 video streams
- Anti-fog with heating glass
- -40°C ~ 70°C operation temperature
- PoE
- IP67 (-FNB only) 3.14

### Specifications

IPC2252-FN/FNB-PIR50-Z2812	
<b>Camera</b>	
Image Sensor	3.5 1/2.8" progressive scan CMOS
Pixels	3.1 1920x1080p ≈ 2,073,600 pixel
Min. Illumination	3.4 Color: 0.002lux @ (F1.6, AGC ON)
	B/W: 0.0002lux @ (F1.6, AGC ON); 0lux with IR
Shutter Speed	1 ~ 1/30,000s
Day / Night	Auto (ICR) / Color / B/W 3.3
Wide Dynamic Range	3.8 Ultra WDR, >=120dB
S/N Ratio	>50dB
White Balance	Auto / Manual
Gain Control	Auto / Manual
Backlight Compensation	Off / WDR / BLC / HLC
<b>Lens</b>	
Mount Type	φ14
Auto Iris	DC drive
Focal Length	3.6 2.8-12mm @ F1.6 motorized varifocal lens
Focus Control	Manual / Semi-Automatic / Auto
Angle of View	95°~ 38°
<b>Infrared</b>	
IR Distance	3.3 50 ~ 70m
IR Intensity	Smart IR
<b>Video</b>	
Compression	3.11 H.265 / H.264 / MJPEG
Image Resolution	3.9 Main stream: 1080p
	Secondary stream: D1
Frame Rate	Main stream: 1080p@30fps 3.2
	Secondary stream: D1@30fps
Bitrate	3.2 32kbps ~ 16Mbps
Bitrate Control	VBR / CBR
Multi-stream	Supported
Caption	Date and time / Alarm / Customized
Privacy Masking	Up to 4 zones
Motion Detection	Up to 4 zones
ROI	Supported
Digital Noise Reduction	3D noise reduction
Digital Defog	Supported
Image Flip	Flip / Mirror / Rotation 90°, 180°, 270°
<b>Network</b>	
Network Protocols	3.16 TCP/IP, UDP, HTTP, HTTPS, DHCP, DNS/DDNS, RTP/RTCP, RTSP, PPPoE, FTP, IGMP, WSIP, UPnP, 802.1x, NAT, QoS, NTP, SMTP, SNMP, IPv4, IPv6 (optional)
User Interface	IPC Control (IE, Firefox, Chrome) 3.12
Max. User Access	3.10 Max. 10 Users (includes 2 internal)
Application Programming	ONVIF (Profile S, Profile G), GB/T 28181-2011, API, CGI
Automatic Network Replenishment (ANR)	Supported
<b>Alarm</b>	
Alarm Triggers	Network disconnect / Disk full / Disk error
Intelligent	Motion detection / Tampering / Guard line / Enter guard area / Exit guard area
Alarm Events	Alarm report / Recording / Text overlay / Snapshot / Email notice
<b>Interfaces</b>	
Ethernet	3.13 10/100M, RJ45 interface
Memory Slot	3.17 Micro SD card slot, supports up to 128GB
<b>Environmental</b>	
Operating Temperature	-40°C ~ 70°C / -40°F ~ 158°F
Operating Humidity	3.15 10% ~ 95%
Protection Level	FN: IP66
	FNB: IP67
<b>Electrical</b>	
Power	12V DC ± 10% / PoE (IEEE802.3af)
Power Consumption	Max. 11W
<b>Mechanical</b>	
Weight	FN: 1kg / 2.2lb (Gross Weight)
	FNB: 1.2kg / 2.65lb (Gross Weight)
Dimensions	FN: 187.3 x 80 x 73mm / 7.37" x 3.15" x 2.87"
	FNB: 271.3 x 80 x 87.8mm / 10.68" x 3.15" x 3.46"
Mounting Bracket	FN: Bracket not included
	FNB: Bracket included

### Dimensions

Units:mm

