

NVR1827-04B

4 Bay Commercial Network Video Recorder



Features

High-performance

- H.265 supported
- 1 x 4K@30fps / 4 x 1080p@30fps video decoding capability
- Up to 32 channels and 4K supported
- Up to 90Mbps incoming bandwidth
- Up to 64Mbps output bandwidth

Small size

- 1.2kg / 2.65lb
- 384 x 199 x 44mm / 15.1" x 7.83" x 1.73"

Easy to install

- Automatic network organizing
- Built-in DHCP server

High reliability


- Embedded Linux
- Low power consumption
- Supports Packet Loss Recovery (PLR)

Abundant functions and features

- Long term recording
- HDMI/VGA simultaneously output different content
- E-Map, TV-Wall supported
- Bi-directional audio, Broadcasting
- NAT
- Alarm management
- Free CMS (V Station), supports 128 NVR simultaneously
- CMS supports 6 screens simultaneously (4 x Live viewing, 1 x E-Map, 1 x TV-Wall)

Dimensions

Units:mm



Specifications

	NVR1827-04016B/16P	NVR1827-040032B/16P	NVR1827-04009B	NVR1827-04016B	NVR1827-04032B
Video/Audio Input					
IP Camera Input	16channel	32 channel	9 channel	16 channel	32 channel
Resolution	8MP(4K), 6MP, 5MP, 4MP, 3MP, 1080p, UXGA, 960p, 720p, XGA, SVGA, D1, CIF, QCIF				
Compression	H.265 / H.264				
Protocols	Onvif, RTSP, KEDACOM				
Incoming Bandwidth	80Mbps	90Mbps	45Mbps	80Mbps	90Mbps
Live Viewing					
Local Display	1 x HDMI, 1 x VGA, simultaneously output different content				
Multi Screen					
Display Local monitor	1/1, 4/4, 1+5/1+5, 1+7/1+7, 9/9, 16/16	1/1, 4/4, 1+5/1+5, 1+7/1+7, 9/9, 16/16	1/1, 4/4, 1+5/1+5, 1+7/1+7, 9/9, 16/1	1/1, 4/4, 1+5/1+5, 1+7/1+7, 9/9, 16/1	1/1, 4/4, 1+5/1+5, 1+7/1+7, 9/9, 16/16
(Main / Secondary):	up to 4 screen simultaneously:				
Display Client	1 ~ 64 Multiple Layouts				
E-Map	Live Viewing in E-Map (V Station)				
Function	E-PTZ / Scheme (V Station) / Virtual channel				
Recording					
Resolution	8MP(4K), 6MP, 5MP, 4MP, 3MP, 1080p, UXGA, 960p, 720p, XGA, SVGA, D1, CIF, QCIF				
Mode	Manual / Continuous / Schedule / Event (Pre / Post) / Long term recording				
Event Trigger	Supported				
Tag	Supported				
Search & Playback					
Search Mode	Date and time (Calendar) / Event				
Resolution	8MP(4K), 6MP, 5MP, 4MP, 3MP, 1080p, UXGA, 960p, 720p, XGA, SVGA, D1, CIF, QCIF				
Playback	1 x 4K@30fps / 4 x 1080p@30fps / 9 x 720p@30fps				
(Local Monitor) Playback(Client)	up to 16 x 4K@30fps				
Synchronize					
Playback (Local Monitor)	4 x 1080p@30fps				
Synchronize					
Playback (Client)	up to 16 x 4K@30fps				
Function	Slow forward / Fast forward / Loop / Single frame / E-PTZ				
Storage					
Max. Internal HDDs	4 x 3.5" HDD				
	Max. 32TB (up to 8TB/each)				
Audio					
Compression	G.711a / G.711u / ADPCM / G.722 / G.722.1c				
Bit rate	32kbps ~ 64kbps				
Audio Function	Bi-directional audio / Dumb / Mute / Broadcasting				
Alarm					
Service Alarm	Alarm input / Video lost / Motion detection / Tampering / Guard line / Defocus / Scene change / Enter guard area / Exit guard area / Object left / Object removal / Gathering / Audio surge				
Triggers					
System Alarm	Device disconnected / No disk / Disk error / IP Address conflict / Network disconnected / Low speed / Insufficient recording space / MAC address conflict / Insufficient snapshot space				
Triggers	Snapshot / Recording / PTZ preset / Buzzer / Email / Link to Client / Alarm caption / Live view in first window / Link to TV Wall / Link to secondary screen / Full screen viewing				
Alarm Events					
System					
Operating System	Embedded Linux				
User Management	Admin / User				
Log Management	User login / User operation / Alarm / Backup / Update				
Application	V Station SDK				
Programming					
Network					
Network Protocols	TCP/IP, UDP, HTTP, DHCP, DNS/DDNS, RTP/RTCP, RTSP, PPPoE, FTP, SNTp, VSPi, UPNP, SMTP, IPv4, IPv6 (optional)				
Viewer Software	CMS (V Station) / Web / iOS app / Android app				
Max. User Access	16 Users				
Output Bandwidth	64Mbps				
Function	NAT / Multiple network access / Packet loss recovery / Auto network organizing				
Network Test	Supported				
Interfaces					
Ethernet	1 x Gigabite network port, RJ45 interface	1 x Gigabite network port, RJ45 interface	1 x 10/100M, RJ45 interface	1 x Gigabite network port, RJ45 interface	
PoE	16 x 10/100M PoE port, RJ45 interface, 15W / each port			/	
Video Out	1 x HDMI (up to 3840 x 2160@60Hz) 1 x VGA (up to 1920 x 1080@60Hz)				
Audio In / Out	1 x RCA Line in / 1 x RCA Line out				
Alarm In / Out	4 x Inputs / 2 x Outputs				
Control	1 x RS485				
USB	2 x USB 2.0				
Environmental					
Operating Temperature	-10°C ~ 55°C / 14°F ~ 131°F				
Operating Humidity	10% ~ 90%				
Electrical					
Power	100 ~ 240V AC, 50 ~ 60Hz				
Power Consumption	Max. 280W (HDD not included)		Max. 15W (HDD not included)		
Mechanical					
Weight	5kg / 11lb (HDD not included)		4.5kg / 9.9lb (HDD not included)		
Dimensions	444 x 410 x 44mm / 17.48" x 16.14" x 1.73"				